

FINGER JOINTED ACCOYA FOR JOINERY

Specification Sheet



KEY FEATURES

Accoya® wood is produced from sustainably sourced, fast growing wood and manufactured using Accsys' proprietary patented modification process from surface to core.

Performance

-  HIGHLY STABLE
-  HIGHLY DURABLE
-  EXCELLENT MACHINABILITY
-  50 YEAR WARRANTY
-  NATURALLY INSULATING
-  FEWER CALL BACKS

Finish

-  BAREFOOT FRIENDLY
-  NATURAL WOOD
-  VERY LOW MAINTENANCE
-  IDEAL FOR COATING

Sustainability

-  LOW CO₂ EMISSIONS
-  NON TOXIC
-  SUSTAINABLY SOURCED
-  LOW ENVIRONMENTAL IMPACT

* U-value advantage over hardwood



ACCOYA FINGER JOINTED SPECIFICATION

Accoya® finger jointed is bonded with EPI adhesive. It offers fixed width, engineered sections for joinery under the KOMO joinery certificate for finger joint quality. Accoya® has been finger jointed under the KOMO scheme successfully since 2007.

Standard Sizes

	*62 x 75	
48 x 100	*62 x 100	*74 x 100
48 x 125	*62 x 125	*74 x 125
48 x 150	*62 x 150	*74 x 150
48 x 200	*62 x 200	*74 x 200

*Indicates subject to availability at the time of ordering.

Lengths

4,200	4,800	6,000
-------	-------	-------

Custom lengths (3,500 to 7,100mm - 10m³ minimum order)

Tolerance

WIDTH	THICKNESS
-1mm / +3mm	+/- 1mm

NOTE: Finger joints are rated for use in non-structural applications and widely used in external joinery. Not suitable for in-ground applications. Accoya finger jointed products require a opaque coating to protect the EPI adhesive.

Finger joint quality certification for opaque joinery use:



Cert. no. 33058/07
BRL 0605 Modified Timber
Accoya® is suitable for in use class 1, 2, 3 and 4 (EN 335-1)

