

ACCOYA® WOODEN WINDOW AND DOOR COMPONENTS

Timber species: “Accoya wood”, (acetylated *Pinus radiata*).

Manufactured by; Accsys Technologies PLC, 4th Floor,
3 Moorgate Place, London EC2R 6EA Tel. 02074 214300

Distributed through; International Timber, James Latham, Arnold
Laver, and other quality timber merchants.

Durability: Class 1. Very durable

Moisture content: Less than 10%

Adhesives: Refer to the latest version of the Accoya
[Wood Information Guide](#)

Contact with metals: Refer to the latest version of the Accoya
Wood Information Guide

Coatings: Two coats of end grain sealer should be used on all
exposed end grain. Any high quality coating system designed for
use on timber can be used on Accoya. A minimum of basecoat(s)
and one topcoat (but ideally the complete system) should be
applied before exposure to moisture. For more details refer to the
Accoya Wood Information Guide and our system suppliers list.

Workmanship: Generally as BS 1186-2:1988 “Timber for and
workmanship in joinery, specification for workmanship”.

Joinery manufacturer to be certified under the Accsys
Technologies Approved Manufacturer Programme.

For further guidance refer to the Accoya wood information guide,
available [here](#) or contact Accsys PLC via www.accoya.com