



Enduring color for Accoya® wood products



Long-lasting, field-applied paints and stains

With over 130 years of experience coating everything from cars and houses to beverage cans and industrial equipment, PPG enhances more high-quality surfaces and substrates in more ways than any other global company.

That's why we're pleased to announce our partnership with Accoya. Accoya modified wood has become a lumber industry benchmark when it comes to performance and sustainability, delivering a unique combination of durability, stability and versatility.

Our PPG SEAL GRIP® primer and PPG ACRI-SHIELD® Max exterior paint system delivers outstanding protection for Accoya products in any of over 2,000 vibrant hues from the PPG VOICE OF COLOUR™ collection. For those looking who want a more traditional stained look, PPG PROLUXE® Log & Siding Wood Finish showcases the natural beauty of the wood in six classic hues.

Our Markets

- Siding
- Decking
- Windows and doors
- Exterior furniture



Mold and mildew resistance

All coatings resist and defend against mold, mildew and fungal growth*
Acri-Shield Max paint provides a 7-year PORTERSEPT® mildew-proof warranty**



Excellent exterior protection

Seal Grip and Acri-Shield Max coatings system delivers stain blocking and weather resistance
ProLuxe finish resists UV rays, cracking and peeling while repelling water



Local availability and delivery

Products available at over 500+ PPG Paints stores nationwide
Job site delivery and other professional services available

* Mold and mildew resistance is limited to the treated surface to provide mold and mildew resistance on the paint film and to inhibit the growth of stain and odor-causing bacteria that may affect the surface of the coating. The use of these products does not protect users of any such treated article or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms.

** This paint contains agents which inhibit the growth of mildew and algae on the surface of the paint film. Subject to exclusions and limitations as set forth in our warranty.



PPG Field-Applied Coatings Products[†]

	Seal Grip Interior/Exterior Universal Primer/Sealer	+ Acri-Shield Max Urethane-Modified Exterior Paint	ProLuxe Log & Siding Wood Finish Transparent Stain
Features and Benefits	<ul style="list-style-type: none"> Helps block out most stains including water, smoke and more Excellent adhesion provides resistance to chipping, peeling and blistering Can be topcoated in as little as one hour Provides a mildew-resistant coating* for defense against mildew and fungal growth 	<ul style="list-style-type: none"> Enhanced durability that stands up to weathering Excellent dirt pick-up resistance <i>Portersept</i> technology inhibits the growth of mold and mildew on the surface of the paint film* Application in temperatures as low as 35°F (2°C) 	<ul style="list-style-type: none"> High-transparency transoxide pigments amplify depth of color, clarity and substrate protection Powerful UV absorbers protect color and wood Flexible resin technology resists cracking and peeling Water repellent Provides a mildew-resistant finish*
Product Type	100% acrylic	Urethane-modified acrylic latex	Alkyd oil
Gloss @ 60°	Flat	Eggshell	Satin
Volume Solids	39% ± 2%	40% ± 2%	58% ± 2%
Weight Solids	52% ± 2%	55% ± 2%	65% ± 2%
Weight	10.6 lbs./gal. (4.8 kg/3.78 L)	11.2 lbs./gal. (5.1 kg/3.78 L)	8.0 lbs./gal. (3.6 kg/3.78 L)
Coverage	400 sq. ft./gal. (37.0 sq. m/3.78 L)	400 sq. ft./gal. (37.0 sq. m/3.78 L)	300-400 sq. ft./gal. (28.0-37.0 sq. m/3.78 L)
Wet Film Thickness, Per Coat	4.0 mils (102 µm)	4.0 mils (102 µm)	N/A
Dry Film Thickness, Per Coat	1.6 mils (41 µm)	1.6 mils (41 µm)	N/A
VOCs	0.7 lbs./gal. (84 g/L)	0.4 lbs./gal. (<50 g/L)	2.9 lbs./gal. (<350 g/L)
Drying Time @ 77° F (25° C) 50% Relative Humidity			
To Touch	30 minutes	1 hour	12 hours
To Topcoat/Recoat	1 hour**	2-4 hours	24 hours
Full Cure	N/A	30 days	N/A

[†] Refer to technical data sheet for more specific information.

* Mold and mildew resistance is limited to the treated surface to provide mold and mildew resistance on the paint film and to inhibit the growth of stain and odor-causing bacteria that may affect the surface of the coating. The use of these products does not protect users of any such treated article or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms.

** For maximum stain resistance, allow 24 hours before applying topcoat.

For more information: accoya.com

This document contains general information only and should not be construed as creating any warranties, express or implied. Please contact a PPG representative for additional information.

The PPG Logo and We protect and beautify the world are registered trademarks of PPG Industries Ohio, Inc. Acri-Shield, ProLuxe and Seal Grip are registered trademarks and PPG Voice of Colour is a trademark of PPG Architectural Finishes, Inc. Accoya and the Accoya trimarque are registered trademarks of Titan Wood Limited. The IN Logo is a registered trademark of LinkedIn Corporation. ©2021 PPG Industries, Inc. All rights reserved. 02/21

