

# Protecting Accoya® Timber



Osmo can be applied to the following:  
Facades (cladding), garden fencing, garden buildings, structures & decking.

## NATURAL INGREDIENTS

The foundation of Osmo wood finishes has been based upon purified and refined natural resources which are carefully harvested natural oils and hard waxes.

## HIGH COVERAGE

With just one tin of Osmo you can achieve near to double the square meter coverage of an ordinary finishing system, saving you time and money.



## MICROPOROUS

The wood remains microporous and continues to absorb and release water without damage. The surface can breathe and becomes anti-static, which attracts less dust and dirt.

## MAINTENANCE

Forget about time consuming, tiring sanding. Osmo natural wood finishes can easily be renovated at any time without the need for sanding.

Care for your treated Accoya exterior products should be managed in line with exposure, use and wear & tear.

Osmo recommends annual inspection & subsequent redecoration works depending on wear. By appropriately topping up the surface at the correct time the Osmo coating performance remains optimal.

*For further advice please contact Osmo.*

## Osmo UK

01296 481220  
sales@osmouk.com  
www.osmouk.com



## A Performance Partnership



THE RIGHT PROTECTION...

...WITH OSMO UK

## Country Colour



- Extremely weather & UV resistant
- Very water & dirt resistant
- Microporous, breathable finish
- No sanding necessary for future applications
- Opaque finish
- 19 colours to choose from



## Natural Oil Woodstain



- Wood grain remains visible
- Durable & hardwearing
- Very water & dirt resistant
- Resists the development of algae, mildew & fungal attack
- Microporous, breathable finish
- No sanding necessary for future applications
- 19 colours to choose from

*Osmo UV-Protection may be used. However, please contact your local stockist regarding application.*

## End Grain Sealing Wax & WR Base Coat



End Grain Sealing Wax:  
- Protects end grain

WR Base Coat  
- Protects against blue stain rot & mildew  
- Unique combination of oil & water that reduces swelling & shrinking and enhances performance

### Protecting Accoya from Fungal & Blue Stain

*We strongly recommend to apply End Grain Sealing Wax & WR Basecoat to Accoya.*

*Before coating, Accoya wood should be clean, dry (below 8% mc) & free of dust, grease & other pollution.*