PROTECTION UV+ for Accoya®



The perfect combination between chemistry and nature

Ultimate Protection^{UV+}

Renner Italia hydro-oils for exterior are long-lasting solutions for the protection of outdoor woodworks. These water-based formulas are created help protect off the attacks from the most dangerous atmospheric and biological agents, thus revolutionizing the concepts of care and maintenance.

In fact, sanding is no longer necessary thanks to the Self-consuming formula of Ultimate Protection UV+. These smart solutions further advance the natural characteristics of Accoya® wood. In addition to the improved longevity and excellent dimensional stability.

Renner Italia hydro-oils make Accoya:

- · highly resistant to water and salty sea mist
- · an incredible shield against UV, fungi, molds and bacteria
- · resistant to abrasion and foot traffic

$Accoya^{\otimes}$

Accoya® is solid wood from sustainable fast-growing forests which provides far excellent dimensional stability and durability performances even superior to the very best tropical hardwoods.

Accoya derives from extensive research concerning the acetylation process. Acetylation is the process used to enhance the properties of wood. In simple terms, it 'pickles' the wood, reducing how much water the cells in the wood can absorb.

Accoya cannot be attached by enzymes, therefore becoming the ideal choice for window frames, exterior doors, cladding, shutters, decking and outdoor furniture.

Accoya is a high-performance sustainable building material.

Choosing Accoya treated with Ultimate Protection UV+ is the best solution for the creation of your woodwork outdoors.







Ultimate coating systems for your Accoya® outdoors

ACCOYA® RESISTANT

COAT	WATER-BASED PROTECTIVE SYSTEM	APPLICATION
1	YS C110 - COLOURED	Brush / Dipping / Flow-coating/ Spray brush
2	YS C110 - COLOURED	Brush / Dipping / Flow-coating/ Spray brush
3	YS C110 - COLOURED	Brush / Dipping / Flow-coating/ Spray brush















ACCOYA® DURABILITY PLUS

COAT	WATER-BASED PROTECTIVE SYSTEM	APPLICATION
1	YS C100/NTR - COLOURED	Brush / Dipping / Flow-coating/ Spray brush
2	YS C100/NTR - COLOURED	Brush / Dipping / Flow-coating/ Spray brush
3	YS M303 (YS M305, YS M307, YS M339) - COLOURED (option: add 5% of YC M402 hardener)	Brush / Spray gun




























- 1. Apply T.Clean RR1050 Detergent by microfiber cloth
- 2. Let it dry off

MAINTENANCE

- 3. Apply T.Clean RR1050 Detergent by microfiber cloth
- 4. Let it dry off
- 5. Apply 1-2 coats by brush of the already applied hydro-oil

A colored coating process is always suggested to obtain the best durability.





Contact us

in fo@renner wood coating s. com



651 Michael Wylie Drive - Charlotte Zip Code 28217 - North Carolina T. +1 704 527 9261

rennerwoodcoatings.com